

Goff's 32 oz. Vinyl


Goff's high performance 32 oz. vinyl has excellent tear strength, tensile strength, and puncture resistance. This heavier vinyl includes extra treatments for UV protection and anti-mildew growth. It is available in a variety of face and stain resistant colors shown below.

	English	Metric	Testing Method
Weight	32 oz./yd ²	1085 g/m ²	FS 5040 / ASTM D3776
Widths	up to 61"	up to 154 cm	
Construction	28 x 26/1" by 1000 x 1000	11 x 10/cm by 1100 x 1100	
Strip Tensile	400 x 340 lbs./1"	1779 x 1512 N/2.5 cm	FS 5102 / ASTM D5035
Tongue Tear	70 x 85 lbs./1"	311 x 378 N/2.5 cm	FS 5134 / ASTM D2261
Adhesion	12 lbs./1"	53 N/2.5 cm	FS 5970 / ASTM D751
Finish	Semi-Gloss		
Cold Crack	-13°F	-25°C	FS 5874 / ASTM D2136
Treatments	Anti-Mildew, UV		
Fire Retardant	Self Extinguishing		Pass

*There are limitations on door size with this material. Please contact Goff's Enterprises for verification of availability.



Black



Light Gray



Tan




Red



Light Green



Light Teal



Light Blue



Yellow



Dark Blue



Purple



700 Hickory Street, Pewaukee, WI 53072

Phone: 800-234-0337 | Fax: 800-959-0170

MADE IN USA goffsenterprises.com | sales@goffscw.com

goffs-materialspecs-32oz.indd | Revised 05.06.21

© 2021 Goff's Enterprises, Inc All Rights Reserved