

800-234-0337 sales@goffscw.com goffsenterprises.com

## Goff's 32 oz. Vinyl Product Properties

Goff's High Performance 32oz. vinyl has excellent tear strength, tensile

strength and puncture resistance. This heavier vinyl includes extra

treatments for UV protection and anti-mildew growth. It is available in a

variety of fade and stain resistant colors.

|                | ENGLISH                   | METRIC                    | TESTING METHOD       |
|----------------|---------------------------|---------------------------|----------------------|
| Weight         | 32 oz./yd²                | 1085 g/m <sup>2</sup>     | FS 5040 / ASTM D3776 |
| Widths         | up to 61″                 | up to 154 cm              |                      |
| Construction   | 28 x 26/1" by 1000 x 1000 | 11 x 10/cm by 1100 x 1100 |                      |
| Strip Tensile  | 400 x 340 lbs./1"         | 1779 x 1512 N/2.5 cm      | FS 5102 / ASTM D5035 |
| Tongue Tear    | 70 x 85 lbs./1"           | 311 x 378 N/2.5 cm        | FS 5134 / ASTM D2261 |
| Adhesion       | 12 lbs./1"                | 53 N/2.5 cm               | FS 5970 / ASTM D751  |
| Finish         | Semi-Gloss                |                           |                      |
| Cold Crack     | -13°F                     | -25°C                     | FS 5874 / ASTM D2136 |
| Treatments     | Anti-Mildew, UV           |                           |                      |
| Fire Retardant | Self Extinguishing        |                           | Pass                 |

\*There are limitations on door size with this material. Please contact Goff's Enterprises forverification of availability.