



**IMPROVING PROFITABILITY THROUGH
FLEXIBLE SPACE SEPARATION**

Manufacturers of the Original Goff Curtain Walls
700 Hickory Street Pewaukee, Wisconsin 53072
Phone: 800-234-0337 Fax: 262-691-3255

Email: sales@goffscw.com Web: www.goffscurtainwalls.com

Dear Valued Goff's Customer:

Thank you for purchasing Goff's Shield All. Below are recommendations. Instructions are printed on the bottle.

If you have any questions or concerns please contact technical support at 800-234-0337.

Spray Gun Recommendations

Conventional spray gun: 1.8-2.0 fluid tip, 40-50 PSI

Gravity feed spray gun: 1.6-2.0 fluid tip, 30-40 PSI

HVLP spray gun: 1.8-2.0 fluid tip, 25-45 PSI

Pressure pot: 10-15 PSI at Pot, 40-45 PSI at gun

Airless: 0.013 orifice, 75-90 PSI

DO NOT FORCE DRY THE SHIELD-ALL!

It will not form a good protective film. Let it air dry.

Shield-All will withstand heated booth bake cycles up to 170 degrees.

How Much Do I Need?

Booths

On average, 1.5 gallons will cover a typical booth, with the dimensions of 14' x 24' x 8'. This will cover the booth with one coat at arm height making the product washable. For a peel-able coating, apply 2-3 coats, letting it air dry between coats.

Curtain Walls

On average, one gallon will cover 400 square feet of curtain. One coat at arm's length will make a washable coating.

When Should I Reapply Shield-All?

If your through-put is:

10 vehicles a month – Re-shield every 90 days

20 vehicles a month – Re-shield every 60 days

30 vehicles a month – Re-shield every 30 days