

Goff's Hydraulic Dock Leveler with Safety Stop Lip



- Simple Push Button Activation
- 10" High Safety Stop Lip
- Structural Steel Deck Supports
- Hydraulic Deck and Lip Cylinders
- Velocity Safety Stop
- Integral Structural Maintenance Strut
- Full Operating Range Toe Guards
- Below Deck End Loading Control
- Safe Hydraulic Lip Extension
- Grease Fittings on Lip Tubes
- Includes (2) Laminated Rubber Dock Bumpers

OPERATION

The Goff's GHDLSSL Series is a hydraulically operated dock leveler. The dock attendant simply pushes the button on the control panel to raise the platform into the "service ready" position. The dock attendant then releases the button and the platform lowers onto the bed of the trailer. Operating range is 12" above and 12" below the dock level.

CONSTRUCTION

The GHDLSSL Series is designed for heavy duty applications and has a capacity range up to 50,000 lbs. All Goff's dock levelers are built with a durable four-sided box construction. The use of structural box beams or "l" beams create considerably more deck strength than other dock levelers.

SAFETY FEATURES

- **10" high safety stop lip** prevents forklift run off on deck surface.
- **Dual cross traffic pedestals** in the event of early departure.
- **Full range toe guards** close off the sides within the service range.
- Integral maintenance strut to support the deck and lip during servicing and cleaning.
- **Structural lip keepers** for cross traffic support and automatic night lock security against theft.

OPTIONS

- Factory Installed Brush Weather Seal
- 18" and 20" Long Lip
- Spray Foam Insulated Deck
- Mushroom Emergency Stop Button
- Custom Bumper Size
- Auto Return to Dock

Platform Size	Capacity	Model	Platform Size	Capacity	Model	Platform Size	Capacity	Model
6′ × 6′	30,000 lbs.	GHDLSSL-6x630	6′ x 6′	40,000 lbs.	GHDLSSL-6x640	6′ x 6′	50,000 lbs.	GHDLSSL-6x650
6′ × 8′	30,000 lbs.	GHDLSSL-6x830	6' x 8'	40,000 lbs.	GHDLSSL-6x840	6' x 8'	50,000 lbs.	GHDLSSL-6x850
6' x 10'	30,000 lbs.	GHDLSSL-6x1030	6′ x 10′	40,000 lbs.	GHDLSSL-6x1040	6' x 10'	50,000 lbs.	GHDLSSL-6x1050
7′ × 6′	30,000 lbs.	GHDLSSL-7x630	7′ x 6′	40,000 lbs.	GHDLSSL-7x640	7′ x 6′	50,000 lbs.	GHDLSSL-7x650
7′ × 8′	30,000 lbs.	GHDLSSL-7x830	7′ x 8′	40,000 lbs.	GHDLSSL-7x840	7′ x 8′	50,000 lbs.	GHDLSSL-7x850
7′ x 10′	30,000 lbs.	GHDLSSL-7x1030	7′ x 10′	40,000 lbs.	GHDLSSL-7x1040	7′ x 10′	50,000 lbs.	GHDLSSL-7x1050

All capacities listed are tested to ANSI MH30.2-2022 Standards