

# **Goff's Mechanical Dock Leveler**



- Simple Pull Chain Activation
- Structural Steel Deck Support
- Heavy Duty Counterbalance System
- Automatic Lip Extension
- Integral Structural Maintenance Strut
- Full Operating Range Toe Guards
- Structural Leg Pedestals/Cross Traffic Support
- Below Deck End Loading Control
- Positive Lip Extension Mechanism
- Grease Fittings on Lip Tubes
- Includes (2) Laminated Rubber Dock Bumpers

#### **OPERATION**

The Goff's GMDL Series is a manually operated dock leveler. The dock attendant simply pulls the release chain at the rear of the platform to release the hold down mechanism. A counterbalance system then raises the deck plate and extends the lip to a "service ready" position. The dock attendant then walks the platform down to the bed of the trailer. If the trailer bed is below dock level, the attendant activates a second pull chain at the front of the deck plate to lower the deck for the lower trailer. Operating range is 12" above and 12" below the dock level.

#### CONSTRUCTION

The GMDL Series is designed for heavy duty applications and has a capacity range up to 40,000 lbs. All Goff's dock levelers are built with a durable four-sided box construction. The use of structural box beams or "I" beams create considerably more deck strength than other dock levelers.

## **SAFETY FEATURES**

- Dual cross traffic pedestals in the event of early departure.
- **Full operating range toe guards** close off the sides within the service range.
- **Integral maintenance strut** to support the deck and lip during servicing and cleaning.
- Structural lip keepers for cross traffic support and automatic night lock security against theft.

### **OPTIONS**

- Factory Installed Brush Weather Seal
- 18" Long Lip
- Spray Foam Insulated Deck
- Custom Bumper Size

Platform Size	Capacity	Model
6' x 6'	30,000 lbs.	GMDL-6x630
6' x 8'	30,000 lbs.	GMDL-6x830
7′ x 6′	30,000 lbs.	GMDL-7x630
7′ x 8′	30,000 lbs.	GMDL-7x830
6' x 6'	40,000 lbs.	GMDL-6x640
6' x 8'	40,000 lbs.	GMDL-6x840
7′ x 6′	40,000 lbs.	GMDL-7x640
7′ × 8′	40,000 lbs.	GMDL-7x840

All capacities listed are tested to ANSI MH30.2-2022 Standards